

HEINE Binocular Loupes

	HR	HRP	HR-C	C
				 C 2.3K C 2.3
Magnification				
2.3x				<input type="checkbox"/>
2.5x	<input type="checkbox"/>		<input type="checkbox"/>	
3.5x		<input type="checkbox"/>		
4x		<input type="checkbox"/>		
6x		<input type="checkbox"/>		
Working distance				
250mm (with close-up lenses)	<input type="checkbox"/>	--	--	--
340mm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
420mm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	--
450mm	--	--	--	<input type="checkbox"/>
520mm	<input type="checkbox"/>	--	--	--
Mounting options				
S-FRAME				
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	--
Lightweight Headband				
	--	--	<input type="checkbox"/>	<input type="checkbox"/>
Professional Headband				
	<input type="checkbox"/>	<input type="checkbox"/>	--	--
Simple Metal Frame				
	--	--	--	<input type="checkbox"/>
Accessories				
Close-up Lenses*	<input type="checkbox"/> (for 340mm)	--	--	--
Protective Lenses	<input type="checkbox"/>	<input type="checkbox"/>	--	<input type="checkbox"/>
LED LoupeLight (Pages 127 / 128)				
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	--
Features				
i-View Function**	<input type="checkbox"/>	<input type="checkbox"/>	--	--
Modular	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	--
Water-resistant	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	--
Achromatic Optics	<input type="checkbox"/>	<input type="checkbox"/>	--	--
Optional Prescription Correction	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	--
Page	118 – 119	120 – 121	122	123

* To reduce the working distance to 250mm.

** i-View function: Provides any angle of view and flips up the optics independently of the illumination beam.